

# BCRP-16 16-Slot POE Media Converter Chassis



## Key Feature

- Up to 16 slots of POE Fiber Media Converters
- 19" standard rack-mount size and 3U height
- Hot-swappable replacement of Media Converters and Power Supplies
- Two redundant power supplies with two cooling fans
- Power isolation design to ensure each bay is electrically isolated from others

## Technical Specifications

Capacity	16 bays for up to 16 POE Fiber Media Converters One hot-swappable power supply(250 Watts)
Power Supply	One hot-swappable power supply(250 Watts) Input: 90~260V/AC, 50~60Hz or DC Power
Cooling	Two internal cooling fans
Dimensions	440 x 300 x 132 mm (W x D x H)
Operating Temperature	0 to 45°C
Storage Temperature	-20 to 70°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class B, CE

Power Supply	BCRP-16-PS Optional second hot-swappable power supply(250W) Input: 90~260V/AC, 50~60Hz or DC Power
Dimensions	150 x 180 x 90 mm (D x W x H)
Operating Temperature	0 to 45°C
Storage Temperature	-20 to 70°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class B, CE

## Order Information

Model Name	Description
BCRP-16	16-Slot Media Converter Chassis with One Power Supply(250W)
BCRP-16-PS	Media Converter Chassis Power Supply for Redundancy(250W)
BCRP-16-2X250	16-Slot Media Converter Chassis with One Power Supply(250W Redundant)
BCRP-16-500	16-Slot Media Converter Chassis with One Power Supply(500W w/o Redundancy)

**Note: In a continuing improvement and update, specifications are subject to change without prior notice.**

